

# P-12 Hydrefiner Drinking Water System

- High Capacity
- Compact
- Reliable

## Get Bottled Water Quality Water Without The Bottle Or The Bother

The P-12 Hydrefiner unit tucks neatly under your sink and dispenses a constant supply, purely delicious water to the RainSoft faucet installed to your sink.

The heart of the system is a highly compressed carbon block filter made of selected activated carbons to reduce tastes and odors, and aesthetic chlorine.

Up to 830\* gallons of drinking water can be produced before the cartridge needs replacement. And when a cartridge change is required, all it takes is a quick turn of the filter body locking ring...and no tools are needed.



2080 East Lunt Avenue  
Elk Grove Village, IL 60007 USA  
847-437-9400  
www.rainsoft.com

A Division of Aquion Partners L.P.

**Distributed by:**

(Each RainSoft dealership is independently owned and operated)



The Hydrefiner Drinking Water System effectively removes or reduces the following contaminants:

- Bad tastes and odors
- Aesthetic Chlorine
- Dirt and dust

**System Features:**

- Compact unit installs conveniently under your sink.
- Rugged stainless steel housing.
- Dual filtration carbon block filter provides a constant supply of highly filtered drinking water.
- 1 micron filtration reduces aesthetic chlorine.
- Available with RainSoft Filtergard II faucet.

\*830 gallons with model 9879: Filtergard II with faucet. 500 gallons with model 9878: Filtergard II without faucet.

## The smart, economical way to solve severe water problems in your home.

### How A Hydrefiner Water Filter System Works:

**Step 1:** Cold water enters the system.

**Step 2:** Water is forced through the tightly compressed activated carbon block filter that has a porosity of only .4 microns.

**Step 3:** Unwanted substances are trapped and filtered out.

**Step 4:** Water leaves the filter and flows through the system's faucet, providing you with an abundant supply of crystal clear, delicious water for both drinking and cooking.

### Hydrefiner System Specifications:

Flow Rate: .75 gallons per minute (2.84 LPM)

Capacity: 830 gallons (1893 liters) with Filtergard II faucet, 500 gallons without faucet

Operating Supply Pressure: 20-100 PS (1.38-6.89 bar)

Operating Temperature: 40-100F (4.4-37.8C)



Hydrefiner P-12 models 9878 and 9879, are certified by NSF to ANSI/NSF standards 42 & 53. Refer to the manufacturer's Performance Data Sheet for specific claims and certifications.

Benefits will be provided by various types of RainSoft equipment when installed and operated according to manufacturer's recommendations. Operational, maintenance and replacement requirements are essential for the product to perform as advertised. All claims based on best available information at time of printing. Manufacturer makes no representations as to the suitability of this equipment for a particular application. Buyer relies entirely on dealer's recommendations in the purchase of this equipment. Independent RainSoft dealers may include, together with your RainSoft product, a product or component that is not manufactured by RainSoft or their parent company, Aquion Partners L.P. Any non-RainSoft product may be covered by the manufacturer of that product, and is not covered by the RainSoft warranty. Aquion Partners L.P. does not warrant that your RainSoft product and the non-RainSoft product will perform properly when used together, and assume no liability therefore.